

Audacious - OLD, PLEASE USE GITHUB DISCUSSIONS/ISSUES - Bug #951

Handle Window manager exit corretly

April 05, 2020 15:45 - Tom Tarson

Status:	Closed	Start date:	April 05, 2020
Priority:	Minor	Due date:	
Assignee:		% Done:	0%
Category:	plugins/qtui	Estimated time:	0.00 hour
Target version:	4.0.1		
Affects version:	4.0		

Description

When the windowmanger exits in KDE for example, QT emits this signal `commitDataRequest`

<https://doc.qt.io/qt-5/qguiapplication.html#commitDataRequest>

and tells the application to save it's current state and then calls the `eventClose` method.

This signal isn't handled in Audacious and if KDE exits, it blocks the logout as it always ignores the event in the `eventClose` method.

Accepting the event always in the `eventClose` method, doesn't block the KDE logout anymore but it would maybe be a better idea to check if `commitDataRequest` was emitted before the `eventClose` method is called.

The patch attached will just always accept the event.

History

#1 - April 05, 2020 15:52 - Ariadne Conill

- Target version set to 4.0.1
- Status changed from New to Closed

I committed an adjusted version of this patch that should match the GTK version's behaviour. It will be in 4.0.1.

Files

kde_exit.patch	356 Bytes	April 05, 2020	Tom Tarson
----------------	-----------	----------------	------------